



TMI INTERNATIONAL, LLC
PHYSICAL PROPERTY DATA SHEET

Product: 01 Compound Flexible PVC
Description: Potable Water Flexible PVC Rolls
.040" to .250" thick
4" to 60" wide
Double polished finish

Property	Typical Value	Test Method
Hardness (15 second delay)	84	ASTM D2240
Tensile Strength	2650 PSI	ASTM D638
Ultimate Elongation	400%	ASTM D638
Graves Tear	435 PPI	ASTM D624
Brittleness Temperature	-17° F -27° C	ASTM D746
Operating Temperature	0 - 150° F	
Specific Gravity	1.24	ASTM D792
UV Resistance	No	

Notes:

CFR Title 21 Compliant

Listed to NSF Standard 61

Each roll is shipped in a box on a 6" core

The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications, or the results to be obtained there from. The information is based on laboratory work with small-scale equipment and does not necessarily indicate end product performance. Full-scale testing and product performance are the responsibility of the user. TMI International, LLC shall not be liable; the customer assumes all risk and liability of any use or handling of any material.

SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without permission of the patent owner.

REV DATE: 02/10/2016 NST

PENNSYLVANIA
1.800.888.9750
5350 Campbells Run Rd
Pittsburgh, PA 15205

OHIO
1.866.929.1449
3333 Win St
Cuyahoga Falls, OH 44223

GEORGIA
1.888.606.7325
4708 S Old Peachtree Rd Ste 700
Norcross, GA 30071

CALIFORNIA
1.800.854.7951
14500 Miller Ave
Fontana, CA 92336