



TMI INTERNATIONAL, LLC  
**PHYSICAL PROPERTY DATA SHEET**

**Product:** 49SB Compound - Flexible PVC  
**Description:** Sound Barrier Flexible PVC Rolls  
.065" to .325" thick  
4" to 60" wide

Property	Typical Value	Test Method
Specific Gravity	1.52	ASTM D792
Hardness (15 second delay)	80	ASTM D2240
Tensile Strength	1400 PSI	ASTM D638
Ultimate Elongation	220%	ASTM D638
Temperature Rating	60° C	

Notes:

The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications, or the results to be obtained there from. The information is based on laboratory work with small-scale equipment and does not necessarily indicate end product performance. Full-scale testing and product performance are the responsibility of the user. TMI International, LLC shall not be liable; the customer assumes all risk and liability of any use or handling of any material.

SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without permission of the patent owner.

REV DATE: 04/12/2016 NST

**PENNSYLVANIA**  
1.800.888.9750  
5350 Campbells Run Rd  
Pittsburgh, PA 15205

**OHIO**  
1.866.929.1449  
3333 Win St  
Cuyahoga Falls, OH 44223

**GEORGIA**  
1.888.606.7325  
4708 S Old Peachtree Rd Ste 700  
Norcross, GA 30071

**CALIFORNIA**  
1.800.854.7951  
14500 Miller Ave  
Fontana, CA 92336