

Toll Free
800-888-9750



Materials Safety
Data Sheet
(MSDS)

Weld Screen & Curtain Film

14 Gauge to 40 Gauge

DPC or DPT: Double Polished Clear or Tinted

2S or 3S: Level of Softness

LD: Lightly Dusted

LC: TMI Exclusive Low Cohesion Formula



SAVE-T® PVC

- ◀ Main Menu
- ◀ Grade Menu

Thickness	Roll Size	Net Roll Weight*	Description	<i>Click for Specifications</i> ↓
<i>Clears</i> .014"	66" x 101 Yds	150 Lbs	DPC-3S-LC-P72	SPEC
	74.5" x 89 Yds	150 Lbs	DPC-3S-LC-P72	SPEC
	66" x 101 Yds	150 Lbs	DPC-3S-LD-P83	SPEC
	74.5" x 89 Yds	150 Lbs	DPC-3S-LD-P83	SPEC
<i>14 mil Weld Tints</i> .014"	<i>Aztec Red, Yellow, Charcoal, Dark Green Shade 8, Blue</i>			
	66" x 101 Yds	150 Lbs	DPT-2S-LD-WCO	SPEC
	74.5" x 89 Yds	150 Lbs	DPT-2S-LD-WCO	SPEC
<i>40 mil Weld Tints</i> .040"	<i>Aztec Red, Amber</i>			
	66" x 36 Yds	150 Lbs	DPT-3S-W83	SPEC

- Ideal for Industrial Curtains
- Complies with OSHA Requirements
- RF Heat Sealable
- Certified Fire Retardant Rating
- Boxed to Ensure Quality
- 3" Inside Diameter Core
- Consult TMI for Samples
- Call for specific details

* Add 12 lbs. to the net roll weight for the gross shipping weight



Available Converting Services

- Rewinding & Put-Up Changes
- Slitting and Sheeting
- Tissue Interleaving

*See Specular Transmission
Graph Below*

Vinyl Solutions
a division of TMI, LLC

5350 Campbells Run Road
Pittsburgh, PA 15205-9738

• fax: 412-787-3665 • web: www.tmivinylsolutions.com • e-mail: vinylsolutions@tmi-pvc.com



Toll Free
800-888-9750
International
412-787-9750

TMI, LLC © 2007