

Dealer: \_\_\_\_\_ Contact: \_\_\_\_\_

**CURTRON PRODUCTS AIR DOOR SUBMITAL**

**1. Air Door Application (Please Circle All That Apply)**

Temperature Control

Wind Control

Bug Control


Dust Control

Is This A: Service Entrance or Customer Entrance (Do You Require 3-Speed Motor Yes / No)


**2. Overall Dimensions of Opening (Width x Height)**

\_\_\_\_\_ ft. \_\_\_\_\_ in. wide x \_\_\_\_\_ ft. \_\_\_\_\_ in. high


**3. Mounting Option (Please Circle One)**




Wall



Ceiling/Threaded Rod



Bracket



Vertical Mount

**Notes: Please Check For Sufficient Clearance And Stable Mounting Environment**

**4. Heating Options (Please Circle One)**

Non-Heated

Electric

Indirect Gas Fired

Steam/Hot Water

**Notes: Electric Heat May Require 3 Phase Power**

**5. Electrical Requirements (Please Circle One)**

120 Volt, 1 Phase

208 Volt, 1 Phase

240 Volt, 1 Phase

480 Volt, 3 Phase

208 Volt, 3 Phase

240 Volt, 3 Phase

**6. Activation Type (Please Circle One)**

Plunger Switch (Hinged Door)

Roller Switch (Sliding/Rolling Door)

Magnetic Reed (Universal)

Remote Mount On/Off Switch

**7. Additional Options (Circle All That Apply)**

Thermostat (For Heated Units)

Time Delay (For High Traffic Areas)

Remote Mount Hand/Off/Auto Switch

**Note: Air Doors Are Not 100% Effective In The Presence Of Negative Pressure**