



Description: **DARK GREEN WELD SCREEN**

## **PRODUCT SPECIFICATIONS**

**SAVE-T PVC STRIP & SHEET**

<b>Roll Size</b>		
<b>THICKNESS:</b>	.040" to .250"	
<b>WIDTH:</b>	4" to 60"	
<b>Material Description</b>		
<b>FINISH:</b>	Double Polished	
<b>COLOR:</b>	Dark Green	
<b>Physical Properties</b>		
<b>Property</b>	<b>Result</b>	<b>ASTM</b>
<b>Hardness (15 sec. delay)</b>	83 A Scale	D2240
<b>Tensile Strength:</b>	2800 PSI	D412
<b>Ultimate Elongation:</b>	330%	D412
<b>Graves Tear:</b>	280	D1004
<b>100% Modulus:</b>	1450 PSI	D412
<b>Stiffness: (-20°F)</b>	-	-
<b>Brittleness Temp:</b>	-34° F	D746
<b>Operating Temp:</b>	0° F to 150° F	-
<b>Specific Gravity:</b>	1.25	D792
<b>Density:</b>	75 lbs. cu.ft.	C-177
<b>Thermal Conductivity (K):</b>	.73	C-177
<b>Thermal Resistance (R):</b>	1.37	C-177
<b>UV Resistance:</b>	YES	
<b>Flammability Rating:</b>	Select Material Compliant with CA State Fire Marshal	
Shipped in a box on 6" cores		

Note: The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy or suitability for particular applications.

**TMI International, LLC**  
5350 Campbells Run Road  
Pittsburgh, PA 15205-9738  
Web-Site: [www.tmi-pvc.com](http://www.tmi-pvc.com)

Toll Free: 800-888-9750  
Phone: 412-787-9750  
Fax: 412-787-3665  
E-mail: [customer-service@tmi-pvc.com](mailto:customer-service@tmi-pvc.com)