



Description: **MARINE - 3S**  
Extruded

## PRODUCT SPECIFICATIONS

### SAVE-T PVC FILM

Roll Size		
THICKNESS:	.030" ; .040" +/- 5%	
WIDTH:	54" + 1/4" -0"	
Material Description		
FINISH:	SUPER DOUBLE POLISHED	
COLOR:	CLEAR	
Physical Properties		
Property	Result	ASTM
Hardness (15 sec. delay)	86 A	D2240
Tensile Strength:	2700 PSI	D412
Ultimate Elongation:	350%	D412
Graves Tear:	490	D1004
100% Modulus:	1580 PSI	D412
Cold Crack:	-20° F	-
Brittleness Temp:	-29° F	D746
Operating Temp:	0° F to 150° F	-
Specific Gravity:	1.24	D792
Density:		
Thermal Conductivity (K):	-	-
Thermal Resistance (R):	-	-
Biocide Additive:	YES ( for Mildew Resistance )	
UV Resistance:	YES	

Note: The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy or suitability for particular applications.

**TMI, LLC**  
5350 Campbells Run Road  
Pittsburgh, PA 15205-9738  
Web-Site: [www.tmivinylsolutions.com](http://www.tmivinylsolutions.com)

Toll Free: 800-888-9750  
Phone: 412-787-9750  
Fax: 412-787-3665  
E-mail: [vinylsolutions@tmi-pvc.com](mailto:vinylsolutions@tmi-pvc.com)