



Description: **PREMIUM NFPA – 3S**
Extruded

PRODUCT SPECIFICATIONS

SAVE-T PVC FILM

Roll Size		
THICKNESS:	.030" to .120" +/- 5%	
WIDTH:	12" to 60" + 1/4" -0"	
Material Description		
FINISH:	SUPER DOUBLE POLISHED	
COLOR:	CLEAR	
Physical Properties		
Property	Result	ASTM
Hardness (15 sec. delay)	85 A	D2240
Tensile Strength:	2950 PSI	D638
Ultimate Elongation:	290%	D638
Graves Tear:	490	D1004
100% Modulus:	1580 PSI	D412
Brittleness Temp:	-17° F	D746
Operating Temp:	0° F to 180° F	D746
Cold Crack:	-10° C	-
Specific Gravity:	1.26	D792
Density:		
Thermal Conductivity (K):	.73	C-177
Thermal Resistance (R):	1.37	C-177
UV Resistance:	YES	
Flammability Rating:	NFPA701	

Note: The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy or suitability for particular applications.

TMI, LLC
5350 Campbells Run Road
Pittsburgh, PA 15205-9738
Web-Site: www.tmivinylsolutions.com

Toll Free: 800-888-9750
Phone: 412-787-9750
Fax: 412-787-3665
E-mail: vinylsolutions@tmi-pvc.com