



Description: **SDPC-3S**  
UV

Inventory Item: G27-20-54-58-118

**PRODUCT SPECIFICATIONS**  
*SAVE-T PVC FILM*

<b>Roll Size</b>			
THICKNESS:	20MIL +/- 5%		
WIDTH:	54" + 1/4" - 0"		
LENGTH:	58 YARDS		
NET WEIGHT:	100 LBS.* +/- 3%		
YARD YIELD:	.58		
<b>Material Description</b>			
FINISH:	SUPER DOUBLE POLISHED		
HAND:	SOFT - 3S		
COLOR:	CLEAR		
<b>Special Features</b>			
UV STABILIZED			
NON-PHTHALATE			
<b>Physical Properties</b>			
<b>Tensile Strength</b> (PSI)	MD	2700	ASTM-D-882
	CD	2500	
<b>Elongation</b> (%)	MD	240	ASTM-D-882
	CD	260	
<b>Tear Strength</b> (Lbs./in)	MD	330	ASTM-D-1004
	CD	330	
<b>Heat Shrinkage</b> (%)	MD	-5	ASTM-D-1004
	CD	+2	
Shipped in a box, rolled in craft paper on 3" I.D. Cores			

\* Shipping weight : Add 12 lbs to net weight

Note: The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy or suitability for particular applications.

**TMI, International, LLC**  
5350 Campbells Run Road  
Pittsburgh, PA 15205-9738  
Web-Site: [www.tmi-pvc.com](http://www.tmi-pvc.com)

Toll Free: 800-888-9750  
Phone: 412-787-9750  
Fax: 412-787-3665  
E-mail: [customer-service@tmi-pvc.com](mailto:customer-service@tmi-pvc.com)