



Description: **3054-SDPC-3S-UV-38**

**PRODUCT SPECIFICATIONS**  
**SAVE-T PVC FILM**

<b>Roll Size</b>			
THICKNESS:	30MIL +0 /-10%		
WIDTH:	54" + 1/4" - 0"		
LENGTH:	19 YARDS		
NET WEIGHT:	50 LBS. +/- 3%		
YARD YIELD:	.38		
<b>Material Description</b>			
FINISH:	SUPER DOUBLE POLISHED		
HAND:	SOFT - 3S		
COLOR:	CLEAR		
<b>Special Features</b>			
UV STABILIZED			
PRINTABLE			
<b>Physical Properties</b>			
<b>Tensile Strength</b> (PSI)	MD	3300	ASTM-D-882
	CD	3200	
<b>Elongation</b> (%)	MD	255	ASTM-D-882
	CD	285	
<b>100% Modulus</b> (PSI)	MD	2200	ASTM-D-1004
	CD	2050	
<b>Heat Shrinkage</b> (%)	MD	-5	ASTM-D-1004
	CD	+2	
Shipped in a box, rolled in craft paper on 3" I.D. Cores			

\* Shipping weight : Add 12 lbs to net weight

Note: The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy or suitability for particular applications.

**TMI International, LLC**  
5350 Campbells Run Road  
Pittsburgh, PA 15205-9738  
Web-Site: [www.tmi-pvc.com](http://www.tmi-pvc.com)

Toll Free: 800-888-9750  
Phone: 412-787-9750  
Fax: 412-787-3665  
E-mail: [customer-service@tmi-pvc.com](mailto:customer-service@tmi-pvc.com)