



PRODUCT SPECIFICATIONS

SAVE-T PVC Coated Polyester Fabric

13 OZ LAMINATED

Spec Sheet # 13L-3-07

Material Description						
Roll Dimensions		English		Metric		
Material Weight		13 oz/yd ² (+/- 4%)		440 gr/sq.m (+/-4%)		
Roll Width		61"		154.9cm		
Roll Length		100 yards		91.44 meters		
Net Weight		138 lbs		62.7 kg		
Base Fabric						
Fiber		Polyester				
Thickness		.019"		0.48 m/m		
Yarn (Denier)		840*840		-		
Fabric Count (threads)		9/9 (fd/inch)		-		
Type of Coating		S-PVC				
Physical Properties						
				Test Method		
		English	Metric	FS-191	ASTM	DIN
Tensile Strength (Strip Method)	Warp	185 lbs/2"	84.1 kg/5cm	FS 5102	ASTM D 5035	DIN 53354
	Fill	167 lbs/2"	75.9 kg/5cm			
Tear Strength (Tongue Method)	Warp	40 lbs	18.2 kg	FS 5134	ASTM D 2261	DIN 53356
	Fill	43 lbs	19.5 kg			
Adhesion Strength		22 lbs/2"		FS 5970	ASTM D 2724	
Temperature Resistance		-22 ~ +160°F	-30 ~ +70°C	-	ASTM D 2136	DIN 53361
Special Features		UV For Exterior Applications, Mildew Resistant NFPA-701 Fire Rated				

Note: The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy or suitability for particular applications.

TMI, LLC
 5350 Campbells Run Road
 Pittsburgh, PA 15205-9738
 Web-Site: www.tmivinylsolutions.com

Toll Free: 800-888-9750
 Phone: 412-787-9750
 Fax: 412-787-3665
 E-mail: vinylsolutions@tmi-pvc.com