

**NEW**

# **SAVE-T<sup>®</sup> LOC**

## **STRIP DOOR HARDWARE**



***The Ultimate  
Strip Door  
System***

- ***Reduces installation time by as much as 75%***
- ***Fits all flat and ribbed strip material***
- ***Strongest and most durable construction***
- ***Patent pending***



 **LLC**  
TMI, LLC

# 1 2 3

## DIFFERENT METALS



TMI, LLC continues to be the leader in the Strip Door industry with the introduction of the revolutionary Save-T LOC hardware.

As with all of our systems, you have the convenience of choosing from galvanized steel, aluminum and stainless steel. All hardware is pre-studded with our patent pending retainer bar locking system.

### Why use Strip Doors with Save-T LOC ?

Strip Doors are the most economical solution to protect employees and goods from adverse conditions such as noise, heat, cold, humidity, dust and drafts. We offer the most diverse range of PVC products, stocking over 450 different types and styles of PVC materials.

The Save-T LOC hardware reduces installation time as the retainer bars quickly lock the strips to the mounting hardware. Since the pins are pre-studded, all that is required is to mount the hardware, attach the PVC strips, then place the retainer bar over the pins and lock into place. It's that simple . . . 1, 2, 3! Unlike our competitors who claim quick installation, the Save-T LOC system is truly quick and durable; the retainer bars with LOC TABS will not come loose in two-way traffic.



With Save-T LOC, installation and replacement of strips is extremely easy. All pins are on 2" centers allowing for replacement with all PVC materials including our patented "RIP-A-STRIP."

# 1 2 3

## DIFFERENT PROFILES


### HEADER Mount Hardware

Model UL-LC




### WALL Mount Hardware

Model SL-LC




### UNIVERSAL Mount Hardware

Model UM/UL-LC



Model UM/SL-LC



# 123

## STEPS TO INSTALL

Save up to 75% installation time



### MOUNT Hardware

Install mounting bar(s) either on the wall above the doorway opening or on the underside of the door lintel.

Time is based on the hardware installation of a typical 8' 0" wide x 10' 0" high doorway opening.



### ATTACH Strips

Place the PVC strips on the Save-T LOC hardware that has just been installed. Refer to our detailed installation instructions for proper overlap configuration.

Time is based on a typical 8' 0" x 10' 0" doorway opening for 12" PVC strips using a 67% overlap.



### PLACE Retainer Bars

Place locking retainer bars over the slotted mounting pins and lock the strips in place.

Time for installation of retainer bars on an 8' 0" wide doorway.

**No tools are required for strip placement or retainer bar attachment.**


# 123

## DIFFERENT THICKNESS SETTINGS

Strips can vary in thickness from .060" to .500". Your application will dictate the size and thickness of PVC.



### The Save-T LOC System



The locking method is patent pending. This mounting method is the easiest, fastest and most durable in the world. Versatility is what sets us apart from our competition.

EXCLUSIVE FLEXIBLE PVC

STRIP & SHEET  
EXTRA THICK PANELS  
FILM MATERIAL

NOISE CONTROL PRODUCTS

MODULAR HARDWARE

SCREENS, CURTAINS & ENCLOSURES

STRIP DOORS

SWINGING DOORS

AIR DOORS

DOCK ACCESSORIES

DESIGN ENGINEERING

TECHNICAL ASSISTANCE



5350 Campbells Run Road  
Pittsburgh, PA 15205-9738

**800-888-9750**

Tel: 412-787-9750

Fax: 412-787-3665

Websites: [www.tmi-pvc.com](http://www.tmi-pvc.com)  
[www.stripdoors.com](http://www.stripdoors.com)

E-Mail: [customer-service@tmi-pvc.com](mailto:customer-service@tmi-pvc.com)

