



Description: **EXTRA LOW TEMP USDA**

**PRODUCT SPECIFICATIONS**  
*SAVE-T PVC STRIP & SHEET*

<b>Roll Size</b>		
THICKNESS:	.120"	
WIDTH:	12"	
<b>Material Description</b>		
FINISH:	Double Polished	
COLOR:	Clear	
<b>Physical Properties</b>		
<b>Property</b>	<b>Result</b>	<b>ASTM</b>
<b>Hardness (15 sec. delay)</b>	63 A Scale	D2240
<b>Tensile Strength:</b>	1650 PSI	D412
<b>Ultimate Elongation:</b>	425%	D412
<b>Graves Tear:</b>	150	D1004
<b>100% Modulus:</b>	700 PSI	D412
<b>Stiffness: (-20°F)</b>	-	-
<b>Brittleness Temp:</b>	-68° F	D746
<b>Operating Temp:</b>	-40° F to 150° F	-
<b>Specific Gravity:</b>	1.17	D792
<b>Density:</b>	75 lbs. cu.ft.	C-177
<b>Thermal Conductivity (K):</b>	.73	C-177
<b>Thermal Resistance (R):</b>	1.37	C-177
<b>UV Resistance:</b>	YES	
<b>Flammability Rating:</b>	Select Material Compliant with CA State Fire Marshal	
Shipped in a box on 6" cores		

Note: The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy or suitability for particular applications.

**TMI International, LLC**  
5350 Campbells Run Road  
Pittsburgh, PA 15205-9738  
Web-Site: [www.tmi-pvc.com](http://www.tmi-pvc.com)

Toll Free: 800-888-9750  
Phone: 412-787-9750  
Fax: 412-787-3665  
E-mail: [customer-service@tmi-pvc.com](mailto:customer-service@tmi-pvc.com)