

Description: **WELD SCREEN**

PRODUCT SPECIFICATIONS

SAVE-T PVC STRIP & SHEET

Roll Size		
THICKNESS:	.040" to .250"	
WIDTH:	4" to 60"	
Material Description		
FINISH:	Double Polished	
COLOR:	Amber / Aztec Red	
Physical Properties		
Property	Result	ASTM
Hardness (15 sec. delay)	83 A Scale	D2240
Tensile Strength:	2800 PSI	D412
Ultimate Elongation:	330%	D412
Graves Tear:	280	D1004
100% Modulus:	1450 PSI	D412
Stiffness: (-20°F)	-	-
Brittleness Temp:	-34° F	D746
Operating Temp:	0° F to 150° F	-
Specific Gravity:	1.25	D792
Density:	75 lbs. cu.ft.	C-177
Thermal Conductivity (K):	.73	C-177
Thermal Resistance (R):	1.37	C-177
UV Resistance:	YES	
Flammability Rating:	Compliant w/ California State Fire Marshal	
Shipped in a box on 6" cores		

Note: The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy or suitability for particular applications.

TMI incorporated
 5350 Campbells Run Road
 Pittsburgh, PA 15205-9738
 Web-Site: www.tmi-pvc.com

Toll Free: 800-888-9750
 Phone: 412-787-9750
 Fax: 412-787-3665
 E-mail: customer-service@tmi-pvc.com