

Description: **STANDARD PANEL**

## PRODUCT SPECIFICATIONS

### SAVE-T PVC PANEL

<b>Roll Size</b>		
<b>THICKNESS:</b>	.275" x .500"	
<b>WIDTH:</b>	36" to 60"	
<b>Material Description</b>		
<b>FINISH:</b>	Double Polished	
<b>COLOR:</b>	Clear	
<b>Physical Properties</b>		
<b>Property</b>	<b>Result</b>	<b>ASTM</b>
<b>Hardness (15 sec. delay)</b>	78A Scale	DIN 53 505
<b>Tensile Strength:</b>	2200 PSI	D638
<b>Ultimate Elongation:</b>	340%	DIN 53 455
<b>Light Transmission:</b>	> 80%	D1003
<b>Operating Temp:</b>	0° F to 130° F	-
<b>Tear Resistance:</b>	300# / In.	D1004
<b>Water Absorption:</b>	<0.2%	DIN 53 495
<b>UV Resistance:</b>	YES	
<b>Flammability Rating:</b>	Compliant w/ California State Fire Marshall	

Note: The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy or suitability for particular applications.

**TMI incorporated**  
 5350 Campbells Run Road  
 Pittsburgh, PA 15205-9738  
 Web-Site: [www.tmi-pvc.com](http://www.tmi-pvc.com)

Toll Free: 800-888-9750  
 Phone: 412-787-9750  
 Fax: 412-787-3665  
 E-mail: [customer-service@tmi-pvc.com](mailto:customer-service@tmi-pvc.com)