

Description: **UCMG-2S-LC-M23**

PRODUCT SPECIFICATIONS

SAVE-T PVC FILM

Roll Size			
THICKNESS:	20MIL +/- 5%		
WIDTH:	54" + 1/4" - 0"		
LENGTH:	58 YARDS; 29 YARDS		
NET WEIGHT:	100 LBS.*; 50 LBS +/- 3%		
YARD YIELD:	.58		
Material Description			
FINISH:	ULTRA POLISHED		
HAND:	SOFT - 2S		
COLOR:	CLEAR		
Special Features			
LOW COHESION			
MARINE GRADE - MILDEW RESISTANT			
UV STABILIZED - 1000 HRS			
-15° F COLD CRACK			
Physical Properties			
Tensile Strength (PSI)	MD	2700	ASTM-D-882
	CD	2550	
Elongation (%)	MD	240	ASTM-D-882
	CD	260	
Tear Strength (Lbs./in)	MD	330	ASTM-D-1004
	CD	330	
Heat Shrinkage (%)	MD	-5	ASTM-D-1004
	CD	+2	
Shipped in a box, rolled in craft paper on 3" I.D. Cores			

* Shipping weight : Add 12 lbs to net weight

Note: The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy or suitability for particular applications.