
PRODUCT SPECIFICATION SHEET

SAVE-T PVC 18 OZ COATED POLYESTER NFPA-701

TYPICAL TECHNICAL PROPERTIES	
BASE FABRIC	POLYESTER
THICKNESS	0.58 M/M
YARN (DENIER)	1000 * 1300, ROUND
THREADS (FD/ INCH)	18/ 17
TYPE OF COATING	E-PVC
WEIGHT (gr./ sq.m)	630
UV STABILIZED	YES
NFPA 701 FIRE RATING	YES
PHYSICAL PROPERTIES	
TENSILE STRENGTH FS5102 (STRIP METHOD)	470 / 485 LBS/2"
ELONGATION FS 5102	27 / 35 %
TEAR STRENGTH FS 5134 (TONGUE METHOD)	90 / 70 Lbs
ADHESION STRENGTH FS 5970 (BOND)	20 Lbs/ 2"
HYDRO-STATIC RESISTANCE ASTMD-751A	660 P.S.I.
ABRISION RESISTANCE ASTM D 3884-92 (LOSS WEIGHT)	.070gr
STANDARD ROLL DATA	
SIZE – YARDS	100
COLD CRACK	-40°C (-40F)
OPERATION TEMPERATURE	MIN -20C (-4F) , MAX 80C (176 F)

Note: The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy or suitability for particular applications.

TMI incorporated
 5350 Campbells Run Road
 Pittsburgh, PA 15205-9738
 Web-Site: www.tmi-pvc.com

Toll Free: 800-888-9750
 Phone: 412-787-9750
 Fax: 412-787-3665
 E-mail: customer-service@tmi-pvc.com