

PRODUCT SPECIFICATION SHEET

SAVE-T PVC 40 OZ COATED POLYESTER

TYPICAL TECHNICAL PROPERTIES	
TOTAL WEIGHT (FS5041)	40 OZ SQ/YD
THICKNESS	0.97 MM
BASE FABRIC	POLYESTER
WEIGHT (gr/sq.m)	1360
DENIER	1000*1000, ROUND
THREADS	31/31 FD/INCH
COATING	
TYPE OF COATING	E-PVC
TOP COAT	ACRYLIC
MILDEW RESISTANT	YES
UV STABILIZED	YES
PHYSICAL PROPERTIERS	
TENSILE STRENGTH FS5041 (STRIP METHOD)	750/ 700 LBS/2"
ELONGATION FS 5102	27 / 35 %
TEAR STRENGTH FS 5134 (TONGUE METHOD)	105 / 90 LBS
ADHESION STRENGTH FS 5970 (BOND)	20 LBS/2"
HYDRO-STATIC RESISTANCE ASTMD-751A	800 P.S.I.
ABRISION RESISTANCE ASTM D 3884-92 (LOSS WEIGHT)	.060 g
STANDARD ROLL DATA	
SIZE – YARDS	50
WIDTH – INCHES	120

Note: The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy or suitability for particular applications.

TMI incorporated
 5350 Campbells Run Road
 Pittsburgh, PA 15205-9738
 Web-Site: www.tmi-pvc.com

Toll Free: 800-888-9750
 Phone: 412-787-9750
 Fax: 412-787-3665
 E-mail: customer-service@tmi-pvc.com