

Toll Free  
800-888-9750



## Low Static Green Tinted Flexible PVC Strip

8" and 12"

FLS: Flat Low Static  
RLS: Ribbed Low Static

*All materials are:*  
Transparent Tinted, Compliant with CSFM Fire Rating,  
UV Stabilized, Recommended for 0° F to 140° F

Click for Specifications → [SPEC](#) or [RIBBED SPEC](#)

Materials Safety  
Data Sheet  
(MSDS)



**SAVE-T® PVC**

- Reduced Static Quality
- Used for Strip Doors
- High Level of Flexibility for Custom Roll Sizes
- Boxed to Ensure Quality
- 6" Inside Diameter Core
- Consult TMI for Samples
- Call for Specific Details
- TMI Can Provide Complete Hardware

- ◀ Main Menu
- ◀ Grade Menu
- ◀ Item Menu

	Strip Width	Model No.	Dimensions	Roll Length(s) in feet
Flat	8"	FLS08080	8" x .080"	150
	12"	FLS12120	12" x .120"	150
Ribbed	8"	RLS08072	8" x .072"/.272"	150
	12"	RLS12072	12" x .072"/.272"	150

\* Listed are commonly stocked items only. All sizes are not shown.

### Available Converting Services

- TMI Exclusive RIP-A-STRIP Converting
- Partial Rolls
- Die Cutting
- Flash Cutting

### Special Orders

Custom Roll Sizes  
from .040" to .500" thick  
& from 3" to 60" wide

Toll Free  
800-888-9750

International  
412-787-9750

TMI, LLC © 2007

**Vinyl Solutions**  
a division of TMI, LLC

5350 Campbells Run Road  
Pittsburgh, PA 15205-9738

• fax: 412-787-3665 • web: [www.tmivinylsolutions.com](http://www.tmivinylsolutions.com) • e-mail: [vinylsolutions@tmi-pvc.com](mailto:vinylsolutions@tmi-pvc.com)

